



# VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,  
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)

E-mail : amit@vibgyorchemtex.com  
\* amit@vibfast.com \* amit@vibfastcolour.com  
Website : www.vibgyorchemtex.com \* www.vibfast.com

Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

## TECHNICAL DATA SHEET

**PRODUCT C.I. NAME.** : **PIGMENT YELLOW 154**  
**VIBFAST BEXIMIDAZOLONE YELLOW 4202**  
**C.I. NO.** : **11781**  
**CUST.TARRIF NO.** : **3204 17 00**

### PHYSICAL PROPERTIES

Density : 1.50  
Moisture Contents : < 1%  
Salt Content : < 1%  
Oil Absorption : ≤ 55  
Sieve Residue (300 Mesh) : 0.5%  
pH Of Aqueous Extract : 7-8  
Heat Stability (°C/5min) : 260-280  
Bulk Volume (L/kg) : 5  
Grit Content : Less than 300 ppm  
Heavy Metal, & PCB Content : Complying to EN 71-3 and AP (89) of European regulation.  
Powder Appearance : Dry Yellow Powder  
Hazardous ingredients : Nil  
Toxicological properties : Non toxic

Shelf Life : 5 Years

### FASTNESS PROPERTIES (1-5) Scale ; 1 Poor - 5 Excellent

Water : 5  
Xylene : 3-4  
Ethanol : 3-4  
Linseed Oil : 4  
Methyl Ethyl Ketone : 4  
Acid : 5  
Alkali : 4

### LIGHT FASTNESS (1-8 Scale ; 1 Very Low - 8 Outstanding)

Full Shade : 7-8  
Tint Shade : 6-7