



VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com
* amit@vibfast.com * amit@vibfastcolour.com
Website : www.vibgyorchemtex.com * www.vibfast.com

TECHNICAL DATA SHEET

PRODUCT C.I. NAME. : **PIGMENT YELLOW 1**
VIBFAST YELLOW 4002
C.I. NO. : **11680**
CUST.TARRIF NO. : **3204 17 00**

PHYSICAL PROPERTIES

Specific Gravity (24°C) : 1.25
Moisture Contents : < 1%
Salt Content : < 1%
Oil Absorption : ≤ 45
Sieve Residue (300 Mesh) : 0.5%
pH Of Aqueous Extract : 7
Heat Stability (°C/5min) : 200
Bulk Volume (L/kg) : 4.5
Grit Content : Less than 300 ppm
Heavy Metal, & PCB Content : Complying to EN 71-3 and AP (89) of European regulation.
Powder Appearance : Dry Yellow Powder
Hazardous ingredients : Nil
Toxicological properties : Non toxic
Shelf Life : 5 Years

FASTNESS PROPERTIES (1-5) Scale ; 1 Poor - 5 Excellent

Water : 5
Xylene : 4-5
Ethanol : 4-5
Mineral Turpentine Oils : 4-5
Linseed Oil : 5
Methyl Ethyl Ketone : 5
Acid : 5
Alkali : 5

LIGHT FASTNESS (1-8 Scale ; 1 Very Low - 8 Outstanding)

Full Shade : 5
Tint Shade : 5