



VIBFAST PIGMENTS PVT. LTD.



C-1, 91/6, Phase I, B/h. Bank of India,
G.I.D.C., Vatva, Ahmedabad - 382 445. (India)
Phone : +91-79-3292 0774, 6450 1424 Fax : +91-79-25893014

E-mail : amit@vibgyorchemtex.com
* amit@vibfast.com * amit@vibfastcolour.com
Website : www.vibgyorchemtex.com * www.vibfast.com

TECHNICAL DATA SHEET

PRODUCT C.I. NAME : PIGMENT GREEN 36
(VIBFAST GREEN 4002)
C.I. NO. : 74265
CUST. TARRIF NO. : 3204 17 00

PHYSICAL PROPERTIES

Density : 1.45
Moisture Contents : <1%
Salt content : < 1%
Oil Absorption : ≤ 25
Sieve Residue (300 Mesh) : 0.5%Max
pH Of Aqueous Extract : 7
Bulk Volume : 2.4
Heat Stability (C/5min) : 200° C
Shelf Life : 5 Years
Heavy Metal, & PCB Content : Complying to EN 71-3 and AP (89) of European regulation.
Grit Content : 300 ppm
Powder Appearance : Green Power
Hazardous ingredients : Nil
Toxicological properties : Non toxic
Tinting Strength : Excellent

FASTNESS PROPERTIES (1-5) Scale ; 1 Poor - 5 Excellent

Water : 5
Xylene : 5
Ethanol : 5
Methyl Ethyl Ketone : 5
Acid : 5
Alkali : 5

LIGHT FASTNESS (1-8 Scale ; 1 Very Low - 8 Outstanding)

Full Shade : 5-6
Tint Shade : 5-6